Product name:	Polyether Polyol YD-310	亚东集 YADONG GROU
Revsion Date	Version	YADONG GROU
20210130	2.0	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Product name:

Polyether Polyol YD-310

Chemical name of the substance:

Glycerol propoxylated

1.2 Relevant identified uses of the substance or mixture and uses advised against

Component(s) for the manufacture of urethane polymers. For industrial use only.

1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION Hebei Yadong Chemical Group Co.Ltd 11F, Block A, 310 Changjiang Avene, Yuhua, Shijiazhuang 050035 Hebei province, P.R.China Customer Information Number: : +86 4006516006 E-mail address: contact@ydchem.cn

Emergency Contact:+86 21 61065388

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2 Label elements

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.3 Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: This product is a substance

No dangerous ingredients according to REACH-Regulation (EC) No. 1907/2006.

Component	REACH Registration Number	CAS No.	Concentration	Classification: REGULATION (EC) No 1272/2008
Glycerol propoxylated		25791-96-2	100%	Not classified

Candidate List of Substances of Very High Concern for Authorisation

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

SECTION 4: First aid measures

4.1 Description of first aid measures

Product name:	Polyether Polyol YD-310	亚东集团 YADONG GROUP
Revsion Date	Version	YADONG GROUP
20210130	2.0	

General advice	First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Inhalation	Take the person into the fresh air and keep him warm, let him rest; if there is difficulty in breathing,
Skin contact:	Wash affected areas thoroughly with soap and plenty of water. Consult a doctor in the event of a skin reaction.
Eye contact:	Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.
Ingestion	If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

- 4.2 Most important symptoms and effects, both acute and delayed: Notes to physician: Basic first aid, decontamination, symptomatic treatment
- **4.3** Indication of any immediate medical attention and special treatment needed No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, extinguishing powder, in cases of larger fires, water spray should be

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen and traces of hydrogen cyanide. In the event of fire and/or explosion do not breathe fumes.

5.3 Advice for fire-fighters

Firemen must wear self-contained breathing apparatus.Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Put on protective equipment (see section 8). Ensure adequate ventilation/exhaust extraction. Keep unauthorized persons away.

Unsuitable extinguishing media

High volume water jet

6.2 Special hazards arising from the substance or mixture

Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen and traces of hydrogen cyanide. In the event of fire and/or explosion do not breathe fumes.

6.3 Advice for fire-fighters

Firemen must wear self-contained breathing apparatus.Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Polvether Polvol YD-310

Version

2.0



Product name:



Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. In all workplaces or parts of the plant where high concentrations of aerosols and/or vapors may be generated (e.g. during pressure release, mold venting or when cleaning mixing heads with an air blast), appropriately located exhaust ventilation must be provided in such a way that the WEL is not exceeded. The air should be drawn away from the personnel handling the product The efficiency of the exhaust equipment should be periodically checked.

In all workplaces or parts of the plant where high concentrations of aerosols and/or vapors may be generated (e.g. during pressure release, mold venting or when cleaning mixing heads with an air blast), appropriately located exhaust ventilation must be provided in such a way that the WEL is not exceeded. The air should be drawn away from the personnel handling the product The efficiency of the exhaust equipment should be periodically checked.

Precautions should generally be taken against electrostatic charges according to the equipment used and the way the product is handled and packaged.

Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at the end of workday. Keep working clothes separately. Change contaminated or soaked clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

Protect from atmospheric moisture. Keep container tightly closed and dry. Avoid prolonged exposure to heat and air. Store in the following material(s): Carbon steel. Stainless steel. Polypropylene. Polyethylene-lined container. Teflon. Glass-lined container. Aluminum. Plasite 3066 lined container. Plasite 3070 lined container. 316 stainless steel.

7.3 Specific end use(s)

See the technical data sheet on this product for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

No information on Exposure Limit Values necessary according to EC directive 2006/121/EG. For technical protective measures to limit exposure see also Section 7 "Handling and storage"

8.2 Exposure controls

Engineering controls

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Respiratory protection

Unless the product is entirely enclosed, do not handle it until you have studied the respiratory precautions issued by the appropriate authority or accident prevention association. If vapors form, respirators must be used. Put on full-mask respirator with filter type ABEK.

Hand protection

Protective gloves are recommended. Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (>= 0.35 mm) Breakthrough time not tested; dispose of immediately after contamination.

Eye protection

Wear eye/face protection

Skin and body protection

Wear suitable protective clothing

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Product name: Polyether Polyol YD-310

Revsion Date

20210130

Version

2.0



9.1 Information on basic physical and chemical properties

Appearance Color 0dor Odor Threshold рH Melting point/range Freezing point Boiling point (760 mmHg) Flash point Evaporation Rate (Butyl Acetate=1) Flammability (solid, gas) Lower explosion limit Upper explosion limit Vapor Pressure Relative Vapor Density (air = 1) Relative Density (water = 1) Water solubility Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature Dynamic Viscosity Kinematic Viscosity Explosive properties Dust explosion class: Oxidizing properties

liquid colorless Odorless to mild No data available 5 - 7Not applicable No data available Literature Decomposes before boiling >150°C No data available Not applicable Not applicable Not applicable Negligible at ambient temperature Not establishe 1.022 Miscible No data available No data available No data available `260 mPa.s@25℃ Not establishe Not explosive Not applicable Not classified as oxidizing.

9.2 Other information

The indicated values do not necessarily correspond to the product specification. Please refer to the product information sheet or the technical information sheet for specification data.

SECTION 10: Stability and reactivity

10.1 Reactivity

This information is not available.

10.2 Chemical stability

No decomposition below initial boiling point

10.3 Possibility of hazardous reactions No hazardous reactions when used as directed.

10.4 Conditions to avoid

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal

10.5 Incompatible materials

Avoid contact with oxidizing materials. Avoid contact with: Strong acids. Strong bases. Avoid unintended contact with isocyanates. The reaction of polyols and isocyanates generates heat.

10.6 Hazardous decomposition product

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon dioxide. Alcohols. Ethers. Hydrocarbons. Ketones. Polymer fragments.

SECTION 11: Toxicological information

Toxicological studies on the product are not yet available.

11.1 Information on toxicological effects

Acute toxicity

Product name: Polyether Polyol YD-310

Version

2.0

Revsion Date 20210130 **亚东集团** YADONG GROUP

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. As product: Single dose oral LD50 has not been determined. LD50, Rat, > 2,000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts. As product: The dermal LD50 has not been determined. LD50, Rabbit, > 2,000 mg/kg Estimated.

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. Vapor from heated material or mist may cause respiratory irritation. For narcotic effects: No relevant data found. As product: The LC50 has not been determined.

Skin corrosion/irritation

Prolonged exposure not likely to cause significant skin irritation. May cause more severe response if skin is abraded (scratched or cut). Material may be handled at elevated temperatures; contact with heated material may cause thermal burns.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

May cause slight temporary corneal injury.

Sensitization

For the component(s) tested:

Did not cause allergic skin reactions when tested in guinea pigs. For respiratory sensitization: No specific, relevant data available for assessment.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

No specific, relevant data available for assessment.

Teratogenicity

No specific, relevant data available for assessment.

Reproductive toxicity

No specific, relevant data available for assessment.

Mutagenicity

In vitro genetic toxicity studies were negative for component(s) tested.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

SECTION 12: Ecological information

Ecotoxicological studies of the product are not available. Do not allow to escape into waterways, wastewater or soil.

12.1 Toxicity

Acute Fish toxicity

Polyether Polyol LC50 6,310 mg/l Species: Danio rerio (zebra fish)

Polyether Polyol YD-310

Product name: Revsion Date 20210130





Exposure duration: 96 h

Acute toxicity for daphnia

Version

2.0

Polyether Polyol EC50 9,890 mg/l Test type: Immobilization Species: Daphnia magna (Water flea) Species: Danio rerio (zebra fish) Exposure duration:48 h Method: ASTM E 729-80

Chronic toxicity to daphnia

Polyether Polyol NOEC (mortality) >= 10 mg/l Species: Daphnia magna (Water flea) Exposure duration:21 d Method: OECD Test Guideline 211

Acute toxicity for algae

Polyether Polyol ErC50 > 100 mg/l endpoint: Growth inhibition Species: Desmodesmus subspicatus (Green algae) Exposure duration:72 h Method: Directive 67/548/EEC, Annex V, C.3.

Acute bacterial toxicity

Polyether Polyol EC50 > 10,000 mg/l Test type: Respiration inhibition Species: activated sludge Exposure duration:3 h Method: Directive 67/548/EEC, Annex V, C.11.

Sediment Toxicity

Polyether Polyol

Due to the low n-octanol-water partition coefficient, an adsorption on the sediment is not to be expected.

Ecotoxicology Assessment

Polyether Polyol Acute aquatic toxicity: The substance is graded as non-critical to water organisms. Chronic aquatic toxicity: A chronic aquatic toxicity is not expected. Toxicity Data on Soil: Adsorbs on soil Impact on Sewage Treatment: Because of the low bacterial toxicity, there is no risk of an adverse effect on the performance of biological waste water treatment plants.

12.2 Persistence and degradability

Biodegradability

Polyether Polyol Test type: aerobic Inoculum: activated sludge Biodegradation: 91 %, 28 d, i.e. readily biodegradable Method: Directive 67/548/EEC Annex V, C.4.D.

Polyether Polyol YD-310

Revsion Date 20210130

Product name:

Version



Stability in water

Polyether Polyol

The study does not need to be conducted since the substance is readily biodegradable.

Photodegradation

Polyether Polyol Test type: Phototransformation in air sensitizer: OH-radicals Concentration sensibilisator: 500,000 1/cm3 Half-life indirect photolysis: 0.063 - 0.12 d Method: SRC - AOP (calculation) After evaporation or exposure to the air, the product will be rapidly degraded by photochemical processes

12.3 Bioaccumulative potential

Polyether Polyo. Due to the low n-octanol-water partition coefficient, an accumulation in organisms is not to be expected

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance does not meet the criteria for classification as $\ensuremath{\text{PBT}}$ or \ensuremath{vPvB}

12.60ther adverse effects

No data available

SECTION 13: Disposal considerations

Dispose in accordance with applicable international, national and local laws, ordinances and statutes.

13.1 Waste treatment methods

After containers have been emptied as thoroughly as possible (e.g. by pouring, scraping or draining until "drip-dry"), they can be sent to an appropriate collection point set up within the framework of the existing take-back scheme of the chemical industry. Containers must be recycled in compliance with national legislation and environmental regulations. None disposal into waste water.

SECTION 14: Transport information	
Classification for ROAD and Rail transport (A	DR/RID):
14.1 UN number	Not applicable
14.2 UN proper shipping name	Not regulated for transport
14.3 Transport hazard class(es)	Not applicable
14.4 Packing group	Not applicable
14.5 Environmental hazards	Not considered environmentally hazardous based on available data.
14.6 Special precautions for user	No data available
Classification for SEA transport (IMO-IMDG):	
14.1 UN number	Not applicable
14.2 UN proper shipping name	Not regulated for transport
14.3 Transport hazard class(es)	Not applicable
14.4 Packing group	Not applicable
14.5 Environmental hazards	Not considered as marine pollutant based on available data
14.6 Special precautions for user	No data available

Product name:	Polyether Polyol YD-310	亚东集团 YADONG GROUP
Revsion Date	Version	YADONG GROUP
20210130	2.0	

14.7 $_{\rm Code}^{\rm Transport \ in \ bulk \ according \ to \ Annex \ I \ or \ II \ of MARPOL \ 73/78 \ and \ the \ IBC \ or \ IGC$

Consult IMO regulations before transporting ocean bulk

	DUIK
Classification for AIR transport (IATA/ICAO)):
14.1 UN number	Not applicable
14.2 UN proper shipping name	Not regulated for transport
14.3 Transport hazard class(es)	Not applicable
14.4 Packing group	Not applicable
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	No data available

Additional information

Not dangerous cargo. Keep dry. Keep separated from foodstuffs.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

Not applicable

15.2 Chemical Safety Assessment

Not applicable

SECTION 16: Other information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.